



BLACK PLUS 55 C

With its well-appointed design, the Black Plus 55 C automotive film combines discretion and privacy from prying eyes with technical efficiency in reflecting solar heat.



SOLAR SCREEN® Warranty
10 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED


WIDTHS AVAILABLE:

- ↔ **51 cm**
- ↔ **76 cm**
- ↔ **101 cm**
- ↔ **152 cm**

Linnanrakentajantie 6, 00810 Helsinki



Sulantie 7 F, 04300 Tuusula




TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	50 %
Reflection of external visible light	8 %
Reflection of internal visible light	7 %
Total solar energy rejected	35 %
Total solar energy rejected 2*	34 %
Solar ratio :	
Solar energy reflection	6 %
Solar energy absorption	34 %
Solar energy transmission	60 %
Reduction in Solar Glare	50 %
g-value	NC
u-value	NC
Shading coefficient	
Installation type : Interior	
Roll length	30,5 m
Film composition	PET
Thickness	50 µ
Colour from the outside : BLACK	

CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

AJANVARAUS (autolasien tummennukset) - info@atummennus.fi tai ☎ 040-5511417
MYYNТИ - info@amainos.fi tai ☎ 045-8025055

INSTALLATION ADVICE

Vertical installation and on standard glass surface*

Clear single pane	✓
Tinted single pane	✗
Reflective tinted single pane	✓
Clear double pane	!
Tinted double pane	✗
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✗
STADIP EXT. clear double pane	✗
STADIP INT. clear double pane	✗

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal shock analysis report.